

Extended Coverage Ordinary Hazard Horizontal Sidewall

Download Extended Coverage Ordinary Hazard Horizontal Sidewall

Thank you definitely much for downloading [Extended Coverage Ordinary Hazard Horizontal Sidewall](#). Most likely you have knowledge that, people have look numerous period for their favorite books once this Extended Coverage Ordinary Hazard Horizontal Sidewall, but stop going on in harmful downloads.

Rather than enjoying a fine book past a mug of coffee in the afternoon, on the other hand they juggled past some harmful virus inside their computer. **Extended Coverage Ordinary Hazard Horizontal Sidewall** is easily reached in our digital library an online right of entry to it is set as public in view of that you can download it instantly. Our digital library saves in merged countries, allowing you to acquire the most less latency era to download any of our books subsequently this one. Merely said, the Extended Coverage Ordinary Hazard Horizontal Sidewall is universally compatible gone any devices to read.

[Extended Coverage Ordinary Hazard Horizontal](#)

F Model MBEC-14 Extended Coverage Ordinary & Extra ...

Extended Coverage Ordinary & Extra Hazard Horizontal Sidewall Sprinklers for Metal Building Applications Bulletin 169 Rev F Bulletin 169 Rev F Model MBEC-14 (SIN R6932) Features 1 Designed to be installed on piping that is supported by the primary structure, not the purlins 2 Provides Extended Coverage Ordinary & Extra Hazard protection

Mode SW-20 an SW-2 11.2 -fator Extende overage rdinar ...

EXTENDED COVERAGE ORDINARY HAZARD HORIZONTAL SIDEWALL SPRINKLER 112 K-FACTOR, 3/4 INCH NPT FIGURE 3 W-TYPE 3 SPRINKLER WRENCH TFP230 Page 3 of 6 NOTES 1 Backwall (where sprinkler is located) by sidewall (length of throw) 2 Requirement is based on minimum flow in GPM from each sprinkler The indicted residual pressures are based on the

Extended Coverage Ordinary Hazard Horizontal Sidewall ...

MODEL SW-20 (TY5332) EXTENDED COVERAGE ORDINARY HAZARD HORIZONTAL SIDEWALL SPRINKLERS 112 K-FACTOR, 3/4 INCH NPT 1-Frame 2 - Button 3 - Bulb 4 - Compression Screw 5 - Sealing Assembly 6 - Deflector * Temperature rating is indicated on deflector ** Pipe thread connections per ISO 7/1 can be provided on special request 1/2" (12,7 mm) NOMINAL

Sees S-3 ry-Type prinkles 11.2K orizontal idewall Standard ...

Ordinary Hazard Horizontal Sidewall, extended coverage use in ordinary 13 Series DS-3 Dry-Type Sprinklers provide protection of coverage areas up to 16 ft x 20 ft (320 ft²) as compared to standard coverage horizontal side-wall sprinklers having a maximum coverage area of 10 ft x 10 ft (100

ft2) for ordinary hazard occupancies NOTICE Series

Extended Coverage Ordinary Hazard Horizontal Sidewall ...

happening bodily one of the favored ebook extended coverage ordinary hazard horizontal sidewall collections that we have This is why you remain in the best website to look the unbelievable books to have extended coverage ordinary hazard horizontal Extended Coverage (Light Hazard) Pendent and Recessed Pendent Sprinklers, K-factor=56 Model SW-20

QUICK RESPONSE CONCEALED EXTENDED COVERAGE LIGHT ...

The Globe Quick Response GL5613 and GL8113 Extended Coverage Horizontal Sidewall Adjustable Concealed Sprinkler for light hazard occupancies, have the lowest profile available for this type of sprinkler, providing an aesthetically pleasing design

EXTENDED COVERAGE SPRINKLERS - Kendall Group

installation rules and for specific light, ordinary, or extra hazard occupancies Extended coverage sprinklers are available in both standard response (EC) and quick response (QR-EC) They are available in upright, pendent, horizontal sidewall and recessed horizontal sidewall These sprinklers are typically used in hotels, restaurants, office

EXTENDED COVERAGE LIGHT HAZARD AUTOMATIC ...

Dec 01, 2017 · extended coverage horizontal sidewall sprinkler temperature rating/classification and color coding extended coverage recessed horizontal sidewall the globe gl8128, gl8129 and gl8174 ex- ordinary intermediate 135°f/155°f 175°f/200°f 57°c/68°c 79°c/93°c orange/red yellow/green 100°f

Extended Coverage Light and Ordinary Hazard

Extended Coverage Upright and Pendent Sprinklers are decorative glass-bulb sprinklers designed for use in light or ordinary hazard occupancies They are intended for use in automatic sprinkler systems designed in accordance with standard installation rules (for example, NFPA 13) for a maximum coverage area of 400 ft² (37,2 m), as

STANDARD RESPONSE TECHNICAL DATA ORDINARY HAARD ...

Order Standard Response Ordinary Hazard Dry Horizontal Sidewall Sprinklers by first adding the appropriate suffix for the sprinkler finish, the appropriate suffix for the temperature rating, and then the suffix for the length ("A" dimension) to sprinkler base part number Order in a specific length noted as the "A" dimension (see

Model G Sidewall Model G/F1 Recessed Sidewall Sprinklers

and the Model G Horizontal Sidewall Sprinkler-HSW1 Deflector provides a very attractive recessed sprinkler for use in light hazard occupancies Model G Extended Coverage Horizontal Sidewall Sprinkler-EC4 Deflector The Model G Extended Coverage Sprinkler is listed for the protection of larger than normal areas in light hazard occupancies

STANDARD/QUICK TECHNICAL DATA RESPONSE ETENDED ...

Extended Coverage Dry Horizontal Sidewall Sprinklers are cULus Listed as indicated in the Approval Chart for installation in accordance with the latest edition of NFPA 13 for extended coverage horizontal sidewall spray sprinklers • Limited to Light Hazard occupancies, with smooth, flat, horizontal ...

Bulletin 160 G Model GFR VELO-ECOH Extended Coverage ...

Extended Coverage Ordinary Hazard Pendent and Recessed Pendent Sprinklers The Reliable Automatic Sprinkler Co, Inc, 103 Fairview Park Drive,

Elmsford, New York 10523 Model GFR VELO-ECOH Pendant & Recessed Pendant (SIN R6043) Features 1 Provides Extended Coverage Ordinary Hazard Protection to 400ft² (372m²) per sprinkler 2

FireLock V36, K5.6 Models V3609, V3610 40

Coverage For coverage area and sprinkler placement, refer to NFPA 13 or applicable standards Plain Horizontal Sidewall Flush Horizontal Sidewall Dry Sleeve & Skirt Horizontal Sidewall Dry Recessed Horizontal Sidewall Extended Horizontal Sidewall Exaggerated for clarity Exaggerated for clarity FireLock® V36, K5.6 Models V3609, V3610 4064 1

QUICK RESPONSE CONCEALED EXTENDED COVERAGE ...

Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500

MODEL SW-20 (TY5332) EXTENDED COVERAGE ORDINARY HAZARD HORIZONTAL SIDEWALL SPRINKLERS 112 K-FACTOR, 3/4 INCH NPT 1-Frame 2 - Button 3 - Bulb 4 - Compression Screw 5 - Sealing Assembly 6 - Deflector * Temperature rating is indicated on deflector ** Pipe thread connections per ISO 7/1 can be provided on special request 1/2" (12,7 mm) NOMINAL

Now Listed and Approved for more types of applications ...

Light Hazard Upright Sprinklers 4 Light Hazard Extended Coverage and Residential Sprinklers 4 Light Hazard Extended Coverage or Residential Pendant Sprinklers 5 Light Hazard Extended Coverage or

Models V2709, V2710 FireLock® V27, K5

Ordinary A 135°F/57°C 100°F/38°C Orange V2709/V2710 Threaded - Ordinary C 8155°F/68°C 100°F/38°C Red V2709/V2710 Grooved - - Intermediate E 175°F/79°C 150°F/65°C Yellow NOTE • 3/16" hex bit provided with V9 coupling shipment Intermediate F 200°F/93°C 150°F/65°C Green High J 286°F/141°C 225°F/107°C Blue

QUICK RESPONSE EXTENDED COVERAGE GL8113 CONCEALED ...

Apr 24, 2017 · ORDINARY INTERMEDIATE 135°F/155°F 175°F 57°C/68°C 79°C ORANGE/RED YELLOW 100°F 150°F 38°C 66°C The Globe Quick Response GL5613 and GL8113 Extended Coverage Horizontal Sidewall Adjust-able Concealed Sprinkler for light hazard occupancies, have the lowest profile available for this type of sprinkler, providing an aesthetically pleasing

Section G Dry Sprinklers - swiftfireprotection.com

Section G - Dry Sprinklers List Price Book - Effective May 3, 2010 Standard Response Standard Coverage Glass Bulb Plain Barrel Pendant SIN: VK150 K Factor: 56 (81)